

METRA MAX 12

Analog-Digital Multimeter

Characteristic Values

Measuring function	Measuring range	Resolution	Input impedance 100 pF // X Ω		Digital display intrinsic uncertainty at reference conditions ±(...% of rdg.+... digits)	Overload capacity ¹⁾		Measuring function
			V _∞ / ~	V _{400kΩ}		Overload value	Overload duration	
V_∞ V_{∞400kΩ}	400.0 mV	100 μV	> 20 MΩ	~400 kΩ	0.75 + 2	600 V effective	continuous	V_∞ V_{∞400kΩ}
	4.000 V	1 mV	11 MΩ	~400 kΩ	0.5 + 2			
	40.00 V	10 mV	10 MΩ	~400 kΩ				
	400.0 V	100 mV	10 MΩ	~400 kΩ				
	600 V	1 V	10 MΩ	~400 kΩ				
V_~ V_{~400kΩ}	400.0 mV	100 μV	> 20 MΩ	~400 kΩ	1.5 + 5	600 V effective	continuous	V_~ V_{~400kΩ}
	4.000 V	1 mV	11 MΩ	~400 kΩ	1 + 5			
	40.00 V	10 mV	10 MΩ	~400 kΩ				
	400.0 V	100 mV	10 MΩ	~400 kΩ				
	600 V	1 V	10 MΩ	~400 kΩ				
			Approx. voltage drop at max. meas. current					
A_∞	40,00 mA	10 μA	450 mV		0.8 + 2	480 mA	continuous	A_∞
	400,0 mA	100 μA	1.5 V					
	10,00 A ²⁾	10 mA	750 mV		1.5 + 5			
A_~	40,00 mA	10 μA	450 mV		1 + 5	480 mA	continuous	A_~
	400,0 mA	100 μA	1.5 V					
	10,00 A ²⁾	10 mA	750 mV		2 + 5			
			Open-circuit voltage					
Ω	400.0 Ω	100 mΩ	approx. 0.5 V		0.8 + 5	600 V effective	5 min	Ω
	4.000 kΩ	1 Ω			0.8 + 2			
	40.00 kΩ	10 Ω						
	400.0 kΩ	100 Ω						
	4000 kΩ	1 kΩ						
40.00 MΩ	10 kΩ	2 + 5						
Ω_Ⓜ	400.0 Ω	100 mΩ			Acoustic signal for 0 ... < 40 Ω			Ω_Ⓜ
→	3.000 V	1 mV	approx. 3 V ³⁾		2 + 10			→
F	4.000 nF	1 pF			3 + 40 ⁴⁾	600 V effective	5 min	F
	40.00 nF	10 pF			3 + 10 ⁴⁾			
	400.0 nF	100 pF			3 + 10			
	4.000 μF	1 nF						
	40.00 μF	10 nF						
Hz⁵⁾	100.00 Hz	0.01 Hz	f _{min} 10 Hz	U _{max} ≤ 600 V	0.2 + 2	600 V effective	continuous	Hz
	1.0000 kHz	0.1 Hz	10 Hz	≤ 100 V				
	10.000 kHz	1 Hz	10 Hz	≤ 40 V				
	100.00 kHz	10 Hz	10 Hz					
	400.0 kHz	100 Hz	100 Hz					

Key: rdg. = measured value (reading)

- 1) At 0 °C ... + 40 °C
- 2) max. 10 A/30 min
12 A/5 min
16 A/30 s
- 3) Battery voltage 2.2 V ... 3.2 V
- 4) With zero adjustment „REL“;
without zero adjustment: +300 digits in the 4 nF range,
+30 digits in the 40 nF range
- 5) Indication of the frequency measurement expanded to up to 9999 digits

Applicable Regulations and Standards

EN 61010-1 VDE 0411-1	Safety regulations for electrical measuring, control, regulation and laboratory devices
DIN 43751	Digital measuring instruments
EN 61326-1 VDE 0843-02-1	Electrical equipment for measurement, control and laboratory use – EMC requirements – Part 1: General requirements
EN 61326-2-1 VDE 0843-02-2-1	Electrical equipment for measurement, control and laboratory use – EMC requirements – Part 2-1: Particular requirements for sensitive test and measurement equipment
EN 60529 DIN VDE 0470-1	Test Instruments and test procedures – Degree of protection provided by enclosures (IP code)

METRA MAX 12

Analog-Digital Multimeter

Reference Conditions

Ambient temperature	+ 23 °C ± 2 K
Relative humidity	40 % ... 60 %
Frequency of measuring quantity	sine 50 Hz
Battery voltage	3 V ± 0.1 V

Display

LCD display field (50 mm x 30 mm) with analog and digital display, and with display of measurement unit, type of current and various special functions.

Analog

Display	LCD scale with bar graph display
Scale length	40 mm
Scaling	0 ... 40 with 40 scale divisions
Polarity display	with automatic reversal
Overflow display	Bar with triangle
Measuring rate	20 measurements/s

Digital

Display/Character height	7 segment digits/ 10 mm
Number of digits	3¾ places \triangleq 3999 steps
Overflow display	„4000“ with flashing „4“
Polarity display	„-“ sign is displayed when plus pole at „1“
Measurement rate	2 measurements/s for U, I and Ω 1 measurement/s for capacitive and frequency measurements



Display

- Digital display with comma and polarity display
- Display for insufficient battery voltage
- Display for REL and HOLD as well as MIN MAX storage
- Continuity test display: speaker symbol appears when acoustic signal is switched on
- Display for diode measurement
- Measurement unit display
- Display for exceeding of measuring range
- Indicator for analog display
- Scale for analog display
- Display for analog or automatic measuring range selection
- Display for selected type of current

Influence Variables and Effects

Influence Variable	Influence Range	Meas. quantity / Meas. range	Influence Effect
Temperature	0 °C ... +21 °C and +25 °C ... +40 °C	V \approx	0.1 x intrinsic uncertainty/K
		V \sim	
		A \approx	
		A \sim	
		Ω	
		F	
		Hz	

Influence Variable	Influence Range (max. resolution)	Frequency	Intrinsic uncertainty at Ref. \pm (... % rdg. +... digits)
Frequency V_{AC}	4, 40, 400 V	20 Hz ... < 50 Hz > 50 Hz ... 500 Hz	2 + 3
	400 mV, 600 V	20 Hz ... < 50 Hz > 50 Hz ... 100 Hz	2 + 3

Influence Variable	Influence Range	Meas. quantity / Measuring range	Influence Effect
Relative humidity	55 ... 75 %	V \approx A \approx Ω F Hz	1 x intrinsic uncertainty

Influence Variable	Interference Magnitude	Measuring ranges	Attenuation
Common Mode Interference Voltage	600 V DC / AC 50 Hz sinusoidal	all V DC	> 100 dB
	600 V DC	all V AC	> 100 dB
	600 V AC 50 Hz sine	400 mV / 4 V AC	> 80 dB
		40 V AC	> 63 dB
		400 V AC	> 43 dB
600 V AC	> 23 dB		
Series-Mode Interference Voltage	max. 600 V AC 50/60 Hz sine	V DC	> 43 dB
	max. 600 V DC	V AC	> 55 dB

Aux. Voltage Influence

(without \rightarrow display) all ranges except AC: ± 5 d
AC range: ± 20 d

Power Supply

Battery	2 ea. 1.5 V mignon cell zinc-carbon cell per IEC R6 alkaline manganese dry cell per IEC LR 6
Service life	zinc-carbon cell: approx. 300 hours Alkaline mang. dry cell: approx. 600 hours
Battery test	Automatic display of „ \rightarrow “ symbol when battery voltage falls below approx. 2.3 V

Power-saving circuit

The instrument switches off automatically when no operating element has been activated for approx. 30 minutes.

Key: rdg. = measured value (reading), d = digit

METRA MAX 12

Analog-Digital Multimeter

Fuses

Fuse for ranges up to 400 mA	FF(UR)1.6 A / 700 V; 6.3 mm x 32 mm; Breaking capacity 50 kA at 700 V ~ and non-reactive load, $\cos \varphi < 0,2$; protects all current measuring ranges up to 400 mA in connection with power diodes
Fuse for 10 A range	FF(UR)16 A / 600 V; 6.3 mm x 32 mm breaking capacity 50 kA at 600 V ~ and non-reactive load, $\cos \varphi < 0,2$

Electrical Safety

Protection class	II per IEC 61010-1:2010/ EN 61010-1:2011/VDE 0411-1:2011	
Measuring category	II	III
Nominal voltage	600 V	300 V
Contamination degree	2	2
Operating voltage	600 V	
Test voltage	3.5 kV~ per IEC 61010-1:2011/ EN 61010-1:2011/VDE 0411-1:2011	

Electromagnetic Compatibility (EMC)

Interference emission	EN 61326-1:2006 class B
Interference immunity	EN 61326-1:2006 EN 61326-2-1:2006

Ambient Conditions

Operating temperatures	-10 °C ... + 50 °C
Storage temperatures	- 25 °C ... + 70 °C (without batteries)
Relative humidity	45 ... 75 %, no condensation allowed
Elevation	up to 2000 m

Mechanical Design

Protection Housing: IP 50, Connector sockets: IP 20
Extract from table on the meaning of IP codes

IP XY (1 st digit X)	Protection against foreign object entry	IP XY (2 nd digit Y)	Protection against the penetration of water
2	≥ 12.5 mm dia.	0	not protected
5	dust-protected	0	not protected

Dimensions W x H x D: 92 mm x 154 mm x 25 mm
Weight approx. 0.2 kg with batteries

Standard Equipment

- 1 Multimeter
- 1 KS14 cable set
- 1 Operating instructions
- 1 Protective cover with tilt stand

Order Information

Designation	Type	Ident. number
Analog-digital multimeter	METRA MAX 12	M212A
Ever-ready bag with cable compartment	F823	GTY3172097P01
Carrying case	F829	GTZ3301000R0003
Fuse set (10 ea.)	FF(UR)1.6A/700V AC	Z109E
Fuse set (10 ea.)	FF(UR)16A/600V AC	Z109A

Edited in Germany • Subject to change without notice • A pdf version is available on the internet

 GOSSEN METRAWATT

GMC-I Messtechnik GmbH
Südwestpark 15
90449 Nürnberg • Germany

DISTRAME

Parc du Grand Troyes - 40 rue de Vienne - 10300 SAINTE-SAVINE
Tél. : 03 25 71 25 83 - infos@distrame.fr - www.distrame.fr